

Technical Data Sheet

Issue date: 11/04/2011 Date last modification: 13/12/2016

GRAPHICS - PROMOTIONAL

4-GL4A-08428 RASO WHITE RP1005 WK135

Face Material

Gloss white acetate satin fabric with very good opacity.

Type Acetate satin fabric

Colour and Finish White

120 g/m² ±10% ISO-536 Weight ISO 534-80 Thickness 140 µ ±10%

Adhesive

Rubber based very aggressive permanent adhesive featuring excellent tack on extremely difficult substrates, especially on apolar materials (like PE and PP).

RP1005 Reference

Type Rubber permanent

Min. Appl. Temp. +5°C

-30°C/+50°C Service Temp. Shear Medium

21 N/25mm FINAT FTM9 Tack Final Adhesion 15 N/25mm FINAT FTM2

This adhesive complies with FDA 175.105.

Liner

One side siliconised clay coated Type

Kraft

Colour and Finish White

Weight 135 g/m² PP-032 - ISO

536 ±10%

145 µ ±10% ISO 534 **Thickness** Transparency DIN 53 147-64 n.a. %

Applications

Fabrics, shoes, cards, mattress labels and promotional stickers.

Printing Methods

Printable in solvent based screenprinting. Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}C \pm 2^{\circ}C$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes. All information is subject to change without prior notice.



